# Improving WAN Performance with XSP GEC12 and SC11 SRS demos

GEC12 – Kansas City, MO

Ezra Kissel

**Martin Swany** 

University of Delaware Indiana University

November 3<sup>rd</sup> 2011





#### Overview

- GENI experiment
  - XSP, Phoebus and SLaBS
- GENI Instrumentation and Measurement project
  - LAMP
- Demos
  - Here, in just a few minutes
  - In two weeks at SC11
    - SC is the conference formerly known as Supercomputing
  - The SCinet Research Sandbox (SRS) will feature an OpenFlow network with switches from HP, IBM, NEC and Pronto (as well as some wide-area 100G experiments)
  - The Disruptive Technologies program will feature Mark Berman

## **eXtensible Session Protocol**

- XSP is a session protocol for IP networks, and provides generalized messaging between gateways, network devices, and services/ applications
  - Addresses the necessity for end to end context while allowing innovation in the core
  - Socket compatible shim library for legacy applications
- In-band and out-of-band signaling makes it ideal for dynamic or software defined networks
  - Dynamic path establishment
  - Provides a channel for application data and/or other metadata to be forwarded with session layer data frames
- Other benefits for future Internet
  - Binding E2E context to the session rather than the transport layer enables location / identification separation
  - Explicit signaling enables rich authentication and authorization support with SSH or X.509

#### Phoebus - SLaBS

- The Phoebus project aims to help bridge the performance gap in modern networks
  - Uses XSP to enable multiple adaptation and buffer points, "gateways", in the network
  - Achieves 10G+ TCP forwarding performance on commodity hardware
  - WAN acceleration
- SLaBS applies burst switching concepts at Phoebus Gateways (PGs)
  - Use XSP to reframe, "slab", incoming flows and send relatively large PDUs versus small layer-3, layer-4 PDUs common today, exchange metadata
- Minimize total transfer time of bulk data flows
  - Latency of individual segments is of less concern
  - Use alternative data channel to improve performance (e.g. RDMA, UDT)


DDRESS RKEY  \$1 0 4 0x68EF  x70df4 13143242  \$2 4 9 0x863B	
0x/0d14 $13143242$ $<$   s2   4   9   $0x863B$	
0x70df4 13143242 s2 4 9 0x863B 0x65a3a 13412431 s3 0xD329	
0x39c4d 24255433	

# Periscope

- Periscope was developed in the LAMP project (GENI I&M)
  - Extended into other efforts with various collaborators
- Measurement control and visualization portal
- Extends and leverages the widely-used perfSONAR system
- Provides caching, aggregation, visualization and control of I&M data

#### **SRS Demo**

- Collaboration with ESnet
- 10G RDMA end-to-end
  - With and without Phoebus
- Bring circuit to endhosts
  - Openflow L2 path setup
- Include GENI resources used at GEC12



## Demo Architecture

