# CleudLab

Tutorial GEC 22 March 2015

#### Today's Plan

- Everyone will build their own clouds
  - Using an OpenStack profile supplied by CloudLab
  - Each is independent, with it's own compute and storage resources
- Log in using GENI accounts
- Create a cloud
- Explore the CloudLab interface
- Use your cloud
- Administer your cloud
- CloudLab is about more than OpenStack

#### Prerequisites

- Account on the GENI portal (sent to you as "pre work")
- Optional, but will make your experience better:
  - SSH keypair associated with your GENI portal account
  - Knowledge of how to use the private SSH key from your laptop
- Known to work best in Chrome and Firefox browsers
- Tablets might work, but not well tested

#### Crash Course in CloudLab

- Underneath, it's GENI
  - Same APIs, same account system
  - Even many of the same tools
  - Federated (accept each other's accounts, hardware)
- Physical isolation for compute, storage (shared net.\*)
- Profiles are one of the key abstractions
  - Defines an environment hardware (RSpec) / software (images)
  - Each "instance" of a profile is a separate
  - Provide standard environments, and a way of sharing
  - Explicit role for domain experts
- "Instantiate" a profile to make an "Experiment"
  - Lives in a GENI slice



# cloudlab.us/tutorial

## CloudLab Hardware






### Utah/HP: Very dense






#### Utah/HP: Low-power ARM64



#### Utah/HP Network: Core switch






#### Utah - Suitable for experiments that:

- ... explore power/performance tradeoffs
- ... want instrumentation of power and temperature
- ... want large numbers of nodes and cores
- ... want to experiment with RDMA via RoCE
- ... need bare-metal control over switches
- ... need OpenFlow 1.3
- ... want tight ARM64 platform integration

### Wisconsin/Cisco





#### Compute and storage

90X Cisco 220 M4

10X Cisco 240 M4





- 2X 8 cores @ 2.4GHz
  - 128GB RAM
  - 1X 480GB SSD
- 2X 1.2 TB HDD

- 1X 1TB HDD
- 12X 3TB HDD (donated by Seagate)

Over the next year: ≥ 140 additional servers; Limited number of accelerators, e.g., FPGAs, GPUs (planned)

#### Networking

Nexus 3132q

Nexus 3172pq





- OF 1.0 (working with Cisco on OF 1.3 support)
- Monitoring of instantaneous queue lengths
- Fine-grained tracing of control plane actions
- Support for multiple virtual router instances per router
- Support for many routing protocols

#### Experiments supported

Large number of nodes/cores, and bare-metal control over nodes/ switches, for sophisticated network/memory/storage research

- ... Network I/O performance, intra-cloud routing (e.g., Conga) and transport (e.g., DCTCP)
- ... Network virtualization (e.g., CloudNaaS)
- ... In-memory big data frameworks (e.g., Spark/Shark)
- ... Cloud-scale resource management and scheduling (e.g., Mesos; Tetris)
- ... New models for Cloud storage (e.g., tiered; flat storage; IOFlow)
- ... New architectures (e.g., RAM Cloud for storage)

#### Clemson/Dell: High Memory, IB

20 cores/node

1 x 40 Gb IB/node

8 nodes/chassis

2\*x 10 GbE OF/node

10 chasses/rack


2\*x 1 GbE OF/node



256 GB RAM/node

2 x 1 TB drive/server

#### Clemson/Dell Network: IB + 10 GbE




#### Clemson - Suitable for experiments that:

- ... need large per-core memory
  - e.g., High-res media processing
  - e.g. Hadoop
  - e.g., Network Function Virtualization
- ... want to experiment with IB and/or GbE networks
  - e.g., hybrid HPC with MPI and TCP/IP
  - e.g., cyber physical system
- ... need bare-metal control over switches
- ... need OpenFlow 1.3


# Building Profiles



#### Copy an Existing Profile




### Use a GUI (Jacks)



#### Write Python Code (geni-lib)

```
two-vm.py (~/Desktop) - VIM
import geni.rspec.pg as pg
rspec = pg.Request()
# Create XenVM nodes
node1 = pg.XenVM("node1")
node2 = pg.XenVM("node2")
# Create interfaces for each node.
iface1 = node1.addInterface("if1")
iface2 = node2.addInterface("if2")
rspec.addResource(node1)
rspec.addResource(node2)
# Create a link with the type of LAN.
link = pg.LAN("lan")
# Add both node interfaces to the link.
link.addInterface(iface1)
link.addInterface(iface2)
```

#### Build From Scratch





# Sign Up



#### Sign Up At CloudLab.us

