GENI Workshop Floating Cloud Tiered (FCT) Network Architecture

Rochester Institute of Technology

Yoshihiro Nozaki, Parth Bakshi, Josh Watts

y.nozaki@mail.rit.edu

1. Floating Cloud Tiered Architecture

- A candidate future Internet architecture
 - Define network clouds and apply tiered model
 - Scalable and Manageable
 - Structure of tiers can be dynamic
 - Flexible, Business models
 - Achieved by new tiered addressing scheme
 - Efficient, Routing, Simple
- Funded by the NSF Future Internet Design research initiative

Floating Cloud Tiered with Routing



Source Cloud ID : 3.1:1:1


Destination Cloud ID: 3.2:2:2 ---> 1.2:2:2


Our Goal with GENI testbed

- Enable real world comparative studies
- Realistic performance analysis
- FCT router is implemented in Linux
 - FCT validation testing
 - FCT performance optimization
- Compare with current routing protocols
 - OSPF
 - BGP
- Transition from IP -> FCT
 - Encapsulate IP packet
 - Use Multi Protocol Label Switching (MPLS)

2. Testbed


- We started from RIT testbed
 - 12 nodes
 - Linux based FCT router
 - Generates FCT packets
 - Forwards FCT packets
- Next, tested in Emulab
 - Expanded network nodes and size
 - Intra-Cloud/Domain level
 - Compare with other protocols





GENI testbed


- Multi-sites nation wide network
 - Both intra- and inter- clouds/domain
 - Near realistic scenarios



GENI testbed


- We have tried to create WEB-based User Interface (Web-UI) for GENI
 - Multiple sites to be established
 - PHP based
 - Used Python test scripts to develop our PHP application
 - Uses Jquery, Codeigniter and some basic Ajax calls
 - Supported most of the GENI API calls
 - PHP function did not work with the CreateSliver API call
 - Encoding method of parameters may be different?

WEB-UI for GENI




WEB-UI

New Interface...



3. Preliminary Results & Feedbacks

- OSPF
- FCT
- OSPF tested using QUAGGA
- FCT using our own code
- Statistics
 - Initial convergence time
 - Node Failure Convergence time
 - Number of Control Packets
 - Data Packets loss during convergence
 - Routing Table size



Issues

Issues

- Availability of number of nodes
- Number of Ethernet ports is limited (5 in Emulab)
 - Control port is dynamically assigned
- Unable to setup native OSPF routing (i.e. gated)

Questions

- Nodes synchronization across sites
- Any standard routing protocols which can be used for comparison study in (multi-sites) test bed
- Statistics Measurements tools