

Distributed Iceberg Detection with SDN-enabled Online Learning

Chang Liu, Shu Ming Peng, Mehdi Malboubi, Chen-Nee Chuah, Matt Bishop, Ben Yoo **University of California at Davis**

This work was partially supported by BBN under the GENI 4 subcontract 1953 under NSF CNS-1346688

> Network Measurement


 Accurate and timely traffic matrix (TM) measurements provide essential inputs for today's various network operations, such as traffic engineering, capacity planning, network troubleshooting and anomaly detection.

> Software Defined Networking (SDN)

- o SDN is considered as a promising element to implement traffic monitoring, management and control.
 - Separation of control plane from data plane
 - . Centralized controller with a network-wide view enabling global optimization
 - Dynamically reprogram switches in a timely manner


> Network Tomography with Online Learning in Software Defined Networks


- Revisit the traffic matrix estimation (TME) problem in OpenFLow-based network.
 - . Limited routing entries & measuring entries
- Utilize the online learning feasibility provided by SDN to target measuring "important" flows
- o Heuristic solutions to allocate "important" flows to distributed TCAM resources



➤ Network Tomography with Online Learning in Software Defined Networks

- o Objective:
 - . Our goal is to estimate the network-wide traffic matrix by collaboratively managing the distributed measurement resources (TCAM entries) in the network.
- - . Install per-flow measurements in the measuring entries to avoid aggregation and routing feasibility issues
 - . Use an intelligent online learning algorithm to sample the most important flows
 - Utilize the online learning feasibility provided by SDN to update the measuring entries periodically to target the most important flows
 - Heuristic solutions to allocate "important" flows to distributed TCAM resources






choose switch j which has the least load end if if $k_i > 0$ then install per-flow measurement for flow fl here $k_i = k_i - 1$

end if 14: end for

>>Simulation Results


- Simulate our framework using GEANT topology
 - . 23 switches, 37 links
 - . Real traffic traces of GEANT network is used
- Application of TME
 - . Heavy Hitter (HH) Detection
 - . Flows with a flow size larger than a threshold
 - . Hierarchical Heavy Hitters (HHH) Detection
 - . Build a prefix tree of source IP address for



Sose, Lavanya, Minlan Yu, and Jennifer Rexford, "Online measurement of large traffic aggregates on commodity switches," Conference on

Hot Topics in Management of Internet, Cloud, and Enterprise Networks and Services-Hot-ICE. USENIX. 2011.





- K_i: number of measuring TCAM entries at each switch
- · NMSE measures the accuracy of traffic matrix estimation

>> Global Iceberg Detection

0.95 ← greedy


0.90


₹ 0.85

0.75

0.70

Global Heavy Hitter (HH) Detection






 Pd_{HH}: probability of detection • Pfa_{HH}: probability of false

. Threshold: 10% of link





- · Threshold: 10% of link capacity
- Recall: the total number of true HHHs detected over the real number of HHHs
- Precision: the total number of true HHHs detected over the total number of HHHs reported